# 0105 Safety Guidance



## **Using the Concrete Mixer**

- 1. Wear protective equipment including ear protection, dust mask, goggles, gloves and safety boots.
- The engine must be running all the time there is a mix in the drum.
- 3. Do not move the concrete mixer while the drum is full.
- 4. Take care when tipping the mixer that you do not cause it to over balance.
- 5. Stop the engine if leaving the machine unattended.
- As soon as work is finished, the mixer and especially the inside of the drum must be washed clean before the mix hardens.
- 7. If the equipment does not work properly do not attempt to repair it. Contact the hire company.
- 8. You may want to read this leaflet again, please keep it safe until you finish







2450 Regents Court










www.hae.org.uk



©Copyright Hire Association Europe April 2011 Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

# 12. To stop the engine turn the ignition switch to the OFF position and close the fuel supply

- 11. Allow the engine to run for a short period to warm up before loading the mix.
- 10. Open the throttle lever to the RUN position. If the engine is now running, shut the choke
- Grasp the pull cord firmly and pull upwards then guide the cord back so that it recoils
- Open the choke lever fully, when starting from cold. Turn the fuel tap to the open position.
- candur clothing or flapping sleeves that could get
- Do not wear gloves when starting the engine. Also, ensure there is no loose clothing or flagging sleeves that could get Check that the throttle lever is in the iule
- 3. Switch the ignition switch to the ON
- Check the oil and fuel levels before starting
- If the hire company has supplied special instructions, follow them. Otherwise, follow the instructions given below. Position the concrete mixer at the work position before

### STARTING THE ENGINE

- Replace all fuel caps properly and move the It sny fuel is spilt on clothes, change them
- the ground, wipe it up or cover it with soil. If very small quantities of fuel are spilt on nei soaked cioth caretully.
- Wipe any fuel off the machine. Dispose of
- prevent petrol seepage when the mixer 6. Do not fill the tank too full; this will help on to the machine. refuelling. Do not spill any fuel on yourself or
- Use a funnel and clean petrol when Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.

3. If possible move the machine away from the Stop the engine and let it cool down.

### **BEFUELLING**

into other parts of the machine grum; the petrol and engine oil may seep Do not leave the mixer standing on the another person.

If the mixer/stand combination is too heavy or if the ground is uneven, seek help from that it stands on the opening of the drum. Locate the stand into position and lock the clip. Tilt the stand and mixer back into the updight position; Make sure it is firmly sited. rinatively one person can tip the mixer so clib.

- Two persons can then lift and locate the mixer onto the stand and secure the locking ground close to the work area.
- 2. The stand should be sited on firm level it easy to empty the drum into a wheelbarrow. The mixer can be used with or without the stand.
- The mixer may be supplied with a stand, which raises the height of the mixer to make into mixer to make into mixer to make into mixer to make the mixer of the mi

- When work is finished, make sure the inside and outside of the drum and the minser are washed clean before the cement mix hardens. Always store and transport the minser in its normal upright position. emptying the mix.
- 4. Ensure the drum remains rotating while powerful. It will not stop rotating until the engine is stopped. Keep hands out of the way. 3. The rotation of the drum is slow but very



- 2. Do not put hands, shovel or anything other than the mix into the drum while it is oad would be more difficult and could put strain on the drum shaft.
- loading. Do not load a concrete mix into a stationary drum. Starting the mixer with a full

- Locate the engine off switch before commencing work with the concrete mixer. beqqots si enigne
- When the engine is started the drum will the totate and will not stop rotation until the bearants si eninne on a flat surface and safely near to your
- at the concrete mixer is sited firmly company.
- Check the engine, mixer, drum and stand, if anythining is found to be damaged, do not use the concrete mixer contact the hire

### CONCRETE MIXER

- Anybody who is working close by will also need to wear identical personal protective
  - Industrial quality gloves must be worn. Sarety boots/wellingtons must be worn.
- of FFP3 protection) must be worn when mixing materials that cause dust. An appropriate dust mask (with a minimum this level as a minimum.
- s up to 96 dB(A) wear appropriate ear so r plugs giving hearing protection for This equipment is likely to cause noise
- sarticular jobs or environments may require a e worn whenever you use this machine.

# **Concrete Mixer**

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment

- 1. It is important to read this entire leaflet before you use the concrete mixer.
- Plan your work and think ahead to make sure you will always be working safely.
- Petrol is highly flammable. Take care not to cause a fire or explosion.
- Cement mixes are harmful to the eyes, lungs and skin. Follow any instructions given by the manufacturers of these cement products
- This concrete mixer is designed for mixing concrete, mortar, plaster and similar compounds with water. It can also mix composts and other similar materials. It is not designed for any other purpose.
- The action of this mixer can cause injury or damage if the machine is not used in a careful and controlled way.
- If you have not used a concrete mixer before, familiarise yourself with how the machine works before you start on the main task.
- You must have at least the following items of personal protective equipment: goggles; dust mask- a minimum of FFP3 protection; ear muffs or plugs giving protection to reduce exposure to 87dB(A) at the ear; Safety boots; industrial gloves.
- A personal first-aid kit should be available.
- This machine must not be used by young persons, or by anyone under the influence of drugs or alcohol.
- This concrete mixer is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.
- Concrete mixers are heavy machines, get help if you have to unload it from your vehicle. Do not lift beyond your own capabilities













ry effort has been made by HAE/EHA to ensure that the information given in this document and supporting mat is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

44 (0) 121 380 4600

rotating.

The Crescent Birmingham Business Park noo sinegen uce

**BAY 788 Iludilos** 



The following items or personal protection equipment (PPE) are the minimum that should **SHOTARING** 

- Make aure your work area is clear and safe and on other persons are close-by and could cause distraction.

  Forder other people from the noise and dust. Set up an exclusion sone around the signs. Work should storp immediately should with physical barriers, barrier tape and with physical barriers, barrier tapes and with the work, ander those directly assisting whork should atop immediately should soryone, other than those directly assisting when using his adultions.

  Clear the sreas of trip hazards e.g. rubble;

  Clear the sreas of trip hazards of rubble;
- Make sure your work area is clear and safe Mechanical extraction ventilation will almost
- petrol, or gas cylinders.

  Using this equipment indoors or in confined spaces could cause **fatal** schoon monoxide poisoning. **Mever** use it in domestic premises and only use it in other indoor premises and only use it in other indoor required has been **fully** assessed.
- Do not use this machine where there is a danger of explosion. It will ignite fumes from netrol. or use evilinders.

"much definition of the first seek medical advice. Learn more about contact, if the reals pensists seek medical advice. Learn more about contact clongs, long sleeves and full trousers should be worn to prevent the mixes coming should be worn to prevent the mixes coming finite contact with bare skin.

skin immediately. Thoroughly rinse eyes and seek medical advice without delay. Mild demaritiis will heal providing there is no turther contact. If the rest nevertes seek causes flaky skin and only occurs where the substance is in contact with the skin... Wash cement or plaster mixes from your skin immediately. Thoroughly rinse eyes

Contact dermalitie is a rash that may occr when the skin reacts to certain substances. The rash can vary but it is usually itchy and

Wet cement mix is a substance that can cause contact dermatitis.

CEMENT MIXES AND CONTACT
DERMATITIS







