



Using the Diamond Drill Rig

1. Wear your protective equipment including dust mask and goggles.
2. Check you are not going to drill into any hidden cables or pipes.
3. Ensure you have adequate water flow to the core drill when drilling.
4. Do not disconnect any water hose until you have switched off, unplugged the drill, and turned off any water tap or valve to stop the flow.
5. Keep the core drill rotating while you are drilling and when withdrawing it.
6. Make sure your core drill is long enough to go right through the wall or floor or the core drill will 'bottom' and will not drill any further.
7. Keep the cable clear of the core drill and any sharp edges on your work.
8. If you think the cable may be cut or damaged in any way, switch off and unplug at the mains before inspecting it. If the cable attached to the diamond drill rig is damaged, stop using the machine. Contact the hire company. If an extension cable has been damaged, do not use it again.
9. Take care not to accidentally pull the plug from the socket.
10. Switch off and remove the plug from the socket before leaving the diamond drill rig unattended.
11. If your equipment does not work properly do not attempt to repair it. Contact the hire company.
12. You may want to read this leaflet again. Please keep it until you finish work.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

230 VOLT MACHINES
(SQUARE PIN OR BLUE PLUG)

1. Use a residual current device ("r.c.d.") plugged directly in to the 230 volt socket. Plug your heater into the rod. This will help to protect you against electric shock if the cable or heater gets damaged.
2. Use the "TEST" button to check that the rod is working each time you use it. Reset the rod according to the instructions supplied with it.
3. If you need an extension cable, follow any special instructions given by the hire company. If the hire company have not given any special instructions, you should only use a suitably rated heavy duty one, not longer than 50 metres (160 feet). Plug it directly into the rod.
4. Lay the extension cable out carefully, avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. Unroll it fully or it will overheat and could catch fire.
5. Make sure that any extension cable connections are dry and safe.

110 VOLT MACHINES (YELLOW PLUG)

1. If you are using a portable transformer, plug the transformer directly into the 230V socket. Do not use any 230V extension cables.
2. If you need to use an extension cable, follow any special instructions given by the hire company. If the hire company have not given any special instructions, you should only use a suitably rated heavy duty one, not longer than 50 metres (160 feet). Plug it directly into the rod.
3. Lay the extension cable out carefully, avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. Unroll it fully or it will overheat and could catch fire.
4. Make sure that any extension cable connections are dry and safe.

BRACING AND ANCHORING

1. If you are core drilling straight into a smooth floor, the vacuum clamp on the machine will normally be strong enough to hold the rig firm.
2. If you are core drilling the floor at an angle, then your rig will need to be further secured by bracing or anchoring.
3. If you are core drilling into walls or ceiling, then you must additionally brace or anchor the rig.

ELECTRICAL SAFETY

Your machine will only operate on one evaporative air cooler.

1. If you are using a portable transformer, plug the transformer directly into the 230V socket. Do not use any 230V extension cables.
2. If you need to use an extension cable, follow any special instructions given by the hire company. If the hire company have not given any special instructions, you should only use a suitably rated heavy duty one, not longer than 50 metres (160 feet). Plug it directly into the rod.
3. Lay the extension cable out carefully, avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. Unroll it fully or it will overheat and could catch fire.
4. Make sure that any extension cable connections are dry and safe.




Before Starting Work...

Diamond Drill Rig

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the Diamond Drill Rig

1. Electricity is dangerous and must always be used with great care.
2. Water and electricity are a hazardous combination. Keep water away from electrical parts.
3. This diamond drill rig is designed to drill large diameter holes in floors, walls and ceilings through reinforced concrete, masonry or stone.
4. The action of this drill can cause injury or damage if the machine is not used in a careful and controlled way.
5. If you have not used a diamond drill rig before, familiarise yourself with the machine first. Practice on some straightforward job before you start on the main task.
6. Plan your work and think ahead to make sure you will always be working safely.
7. You must have at least the following items of personal protective equipment: impact resistant goggles: EN166 - B or BS2092 grade 1; dust mask - a minimum of EN149 FFP3(s) protection; ear muffs or plugs giving protection for levels up to 86 dB(A); gloves; rod if using a 230 volt (mains) supply.
8. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
9. This diamond drill rig is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

WORK AREA

1. Do not use this diamond drill rig where there is a danger of explosion, or gas, cylinders.
2. Make sure that the area is clear and safe and that no-one is near to you or could distract you.
3. Protect other people from the noise, and debris. Warn others to keep away. Put barriers around your work area.
4. Check that there are no hidden electric cables, gas or water pipes where you are drilling.
5. Check you have an adequate, clean water supply either from the mains or from a water tank.
6. Make sure the waste water will not cause damage. Check if the hire company supplied water collection equipment, use it.

OPERATORS

1. The following items of personal protective equipment (ppe) are the minimum that should be worn wherever you use this machine. Particular jobs or environments may require a higher level of protection.
2. You must impact resistant goggles (EN166 - B or BS2092 grade 1) when you are working with this machine.
3. This equipment is likely to cause noise levels up to 86 dB(A) - wear appropriate ear muffs or plugs giving hearing protection for this level as a minimum.
4. You will need to wear an appropriate dustmask (with a minimum of EN149 FFP3(s) protection) to protect yourself from spray, mist or dust.
5. Anybody who is working near to you will also need to wear appropriate personal protective equipment.

DIAMOND DRILL RIG

1. Check your machine, cables and plugs and all other equipment. If anything is found damaged, do not use it.
2. Use only the correct grade core drills as recommended by the hire company for the material being cut.
3. Make sure that your core drill is long enough to go right through the wall or floor to be drilled. Remember the 'core' of the brick or masonry remains inside the core drill until you switch the diamond drill rig off, and unplug it before changing the core drill.

CORE DRILLS

1. Switch the diamond drill rig off, and unplug it before changing the core drill.
2. Make sure you understand all of the controls. Before you switch the diamond drill rig on, you must know how to stop it.
3. Your machine may operate at more than one speed and you may be able to set the core drill to rotate clockwise or anticlockwise. Ensure you have the right settings before you start work.
4. Make sure you understand all of the controls. Before you switch the diamond drill rig on, you must know how to stop it.
5. Make sure you understand all of the controls. Before you switch the diamond drill rig on, you must know how to stop it.