

Before Starting Work.

AAHA XHOW

danger of explosion. It will ignite fume petrol, or gas cylinders. Do not use this turf liter where there is a

- eathing toxic fumes do not run the inside a building or closed space ດມເດີ່ມດ To reduce the risk of serious or fatal injury .s
- Protect other people from the noise and from injury. Erect barriers, fasten a rope, or tape barrier around the area to be cut to warm 3 unless the area is well ventilated.
- Take extra precautions to keep children and others to keep away.
- ·9 vers away.
- гягде we •0 Make sure the area where you are about to cut is clear t stones, pieces of wood, or anything else that may interfere with the operation for the machine, wear your gloves to do this.
- ·oum ners und weeds with deep roots or long grass will in the turf lifter from operating properly; rass should be reasonably short before test lifting ne diass
- The machine should not be used in stony

nunnin

96H

- equipment (ppe) are the minimum that should be worn whenever you use this turt litter. The tollowing items of personal protective **SROTARAGO**
- .s higher level of protection. st jobs of environments may require a
- plugs giving hearing protection for this level This equipment is likely to cause noise levels up to 96 dB(A) – wear appropriate ear mufts or up to 96 dB(A) – wear appropriate ear mufts
- BS1870/4972) giving good foot and ankle You must wear safety boots (EN345 or 31 unminim
- You will need strong gloves to handle any rubbish or debris on the ground. The gloves °t
- N JOU OG olood circulation. o keep your hands warm, improving
- avioand isnosiad analogidad is Anybody who is working near to you will also -9 Do not wear any loose clothing that could get caught in the machine.
- nuouudinhe

3YT TEB Iludilos

The Crescent Birmingham Business Park มกอา รมมอติอม กระว Association Europe

:lism3 :euoudeie

-1

-7

-9

·9

÷ŧ

.s

ວ່າດມ

әч⊥ 3

ΝΟΙΤΑΆΒΙΥ

vuse.org.u

now to control and stop it.

turf lifter will stop moving.

יסופ וסכאונוס כוולד נס שום צושניונוסי

machine without assistance.

rue une company.

TURF LIFTER

44 (0) 121 380 4600





hazardous. Warm your hands up before you start work, and wear gloves to keep your hands warm while you are working.

Vibration from using this turf lifter can be

Make sure you understand all of the controls. Before you start the turt lifter, you must know

telease the control levers and the machine vill immediately stop.

If the turf lifter gets out of control while working, do not fight to regain control.

unse the centrifugal clutch to disengage and

In either case, the engine will slow to idle speed if you release these controls. This will

To control the engine speed, you will have either a throttle twist grip or a hand lever on the handlebars; the hand lever also has a fast-idle locking clip to ald starting

Tot come into operation until the engine speed is increased. This means that I the angine is increased. This means interfact angine is remainible to a speed the provide the speed is the speed of the s

Other models transmit only enough drive to assist the machine being pushed. Some house sprovide enough drive to move the machine without assistance

On some models, there is NO drive to the wheels and the must be pushed.

engine, control cables and levers, the cutting blade, and the tyres. If anything is found damaged, do not use the turt lifter - contact

Check your turf lifter thoroughly, including

drive is transmitted tot eh wheels and le by a centrifugal clutch. The clutch does

44 (0) 121 333 4109

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia In this been made by the provide the ensure that the information given in this document and support is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perce-nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins irom the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law. to have arisen t



3

5.

- This machine must not be used by minors or by anyone under the influence of drugs or alcohol.
- This turf lifter is designed for operation by an able bodied adult. Anyone with either temporary of 10

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

Turf Lifter

FTH HIRE GROUP

v:112016

Plan how to tackle the job and try to foresee any problems that may occur, such as checking for cables or pipes that may be buried just below the surface where you are going to cut so that you can safely avoid any injury or damage

1644 Safety Guidance

4 STROKE PETROL

- 2
 - Petrol is highly flammable. Take care not to cause a fire or explosion This turf lifter produces vibration while in operation - see notes under

the section headed "vibration"

- This turf lifter is designed to neatly cut and lift a strip of turf, across a lawn or other level expanse of
- grass. The complete root system can be lifted in order to allow re-laying.
- This turf lifter may cause injury to persons or damage to property if it is not handled and used carefully
- and properly.
- Keep your hands and feet away from all moving parts while the machine is in operation. 6.
- 7. If you have not used a turf lifter before, practice on an unimportant piece of grass until you are confident
- that you can use the turf lifter safely
- You must have at least the following items of personal protective equipment: ear muffs or plugs giving protection for levels up to 97 dB(A); safety boots (EN345 or BS1870/4972) to protect feet and ankles;

permanent disability must seek expert advice before using it.







- 1.
- Lift the blade clear before moving the turf lifter over paths and borders 2

Walk over the cut grass carefully while working to avoid damaging it.

3. Hold the turf lifter handle firmly with both hands while working.

Do not attempt to cut on steep gradients.

the grass you have just cut.

the turf into manageable sections

Stop the engine before leaving the machine unattended.

them out of the way.

been removed.

7.

8

9.

10.

12.

13.

14.

15. 16.

17.

18.

19.

20.

HJE

4. Do not lower, or activate the blade on any hard surface. The blade will be damaged and injury could occur

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

1

- 5. The engine must be running fast enough to activate the blade before you lower it into the ground. If cutting on a slope do not work up and down the slope. Start at the top and work across the slope. 6.

Make sure you are cutting deep enough to remove the complete root system if you are going to re-lay

While cutting, keep a lookout for any stones or other objects in your path. Stop the turf lifter and clear

Before attempting to remove wire tangled round the blade or grass binding a wheel or any similar fault,

stop the engine by closing the throttle and switching the ON/OFF switch to OFF, then remove the spark

This allows the machine to operate on the level rather than one side being lower where the grass has

If the strip of turf is too long and too heavy to handle use a border spade or other edging tool to cut

plug lead from the spark plug to prevent the engine from starting until you have rectified the fault.

11. If cutting more than one strip of grass, leave the strip just cut in place until you cut the adjacent strip

The turf lifter can be steered to cut round gentle curves if the layout of the lawn so required.

Clean the machine at the end of each day and before you return it to the hire company.

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

44 (0) 121 380 4600

e.org.uk

or cover it with soil.

No smoking.

BEFUELLING

nsuer

uguqieps

CUTTING BLADE

v spnsr

s uO .s

.,

-9

.2

.4

3

.S

.۴

3

3

.2

44 (0) 121 333 4109

It you spiil any tuei on the ground, when it up

Wipe any fuel off the machine. Dispose of fuel soaked cloth carefully.

Do not spill any fuel on yourself or the

Des a tunnet and clean petrol when retueting.

Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.

Move the machine away from your work area

Make sure the blade is lifted clear while maneuvering the turt lifter into position and

to a pre-set depth by lifting or lowering the spring tensioned handlebars. These handlebars can be folded over for easier transit

On other models, the cutting blade is moved

The cutting blade depth is set by lifting and

couring wearing your gloves to keep your

To help prevent vibration affecting your hands, operate the rug lifter for shorter periods;

Watch out for signs that vibration may be affecting your hands. If your fingers start to imgle or feel numb, take a short break from using the turt lifter. Exercise your fingers to agroup short dividiation

are, these handlebars can also be

ele located in the centre of the

Stop the engine and let it cool down.

พบคม ธเสนเมดิ เมค คมดิเมค.

rubieu jot peisujar.

owering the rear wheels.

noulade piood circulation.

You may want to read this leaflet again. Please keep it until you finish work.

Hire Association Europe

ngham Business Park

2450 Regents Court The Crescent

olibull B37 7VE

Anich the ignition switch to OFF.

12. As soon as the engine is warm set the choke

11. In cold weather, you may need to let the engine warm up by gently opening the throttle, before starting work.

choke controls are in the correct position. Pull

Guide the cord back into place so that it

it quickly and strongly. Don't pull it too far, or the cord may break.

With your other hand, pull out the starting cord handle slowly until you can feel that the starter has engaged with the engine, then pull

Hold the machine firmly with one hand, so that it will not move when you pull the starting

die; others have a fast idle setting on the incitie control.

Some models will start with the infotule set at

It your machine has a tuel tap, open it. In cold conditions. You may also need to set the

Check that the spark plug lead has been

Check that the blade is lifted clear of the

If the hire company has given you special instructions for your turi lifter, follow them. A subscript of the provided and the

This section describes the starting procedure

Put all fuel caps back on properly, and move your fuel can to a safe, cool place.

It you spill any tuel on your clothes, change them straight away.

replaced and is securely on the spark plug.

cient petrol, and that the throttle

10. If the engine did not start, check that there is

Close the throttle.

O of lotino

Turn the tuel tap off.

STOPPING THE ENGINE

the starting cord again.

recoils correctly.

.6

.8

.7

.9

'G

3

.s

1 **DNITRATZ**

.6

.8

. D100

(alb)

.o. Buonuq

choke control.

for most turf lifters.

Using the Turf Lifter