Useful Reference Points • www.hae.org.uk/businessguard

Betore Starting Work.

orper

OL

AAHA XHOW

- cylinders. It will ignite fumes from petrol, or gas where there is a danger of explosion. Do not use this vacuum cleaner 1
- and animals well clear. or could distract you. Keep children safe and that no-one is near to you 2. Make sure that the area is clear and
- .ıəw where the electrical parts might get Do not use this cleaner in the rain or 3.

VACUUM CLEANER

tatutory Instruments

- company. vacuum cleaner- contact the hire is found damaged, do not use the plugs and all equipment. If anything 1. Check your equipment, cables,
- improvise them. not try to force connections or edulpment matches your supply. Do 2. Check that the plug on your
- than you think. Equipment designed moving it about - it may be heavier care not to injure yourselt when transformer has been supplied, take mains 230v supply. If a portable power the equipment from a normal portable transformer if you need to hire company will have provided a run off a special 110v supply. The industrial plug fitted is designed to Equipment with a cylindrical yellow - 2

to run directly from 230v mains will

มกอา ระบอดอา กระ HILE ASSOCIATION EUROPE

3YT TEB Iludilos The Crescent Birmingham Business Park

:lism3 :euoudeie

voltage; it will be 110v or 230v.

YTERCAL SAFETY

u dois oi wou

overheat rapidly.

and may damage it.

nazardous materiais.

involving asbestos

.6

.8

-2

-9

'G

·t

.Ilut si

110V equipment will have a yellow

230v equipment will have either a normal

Your equipment will only operate on one

vacuum cleaner on, you must know

operates. Before you switch the

9. Check on how the on/off switch

passage causing the machine to

full, the ball valve will shut off the air

It the waste container becomes too

Empty the waste container before it

sludge, it will clog up the machine

Do not try to clean up waste oil or

flammable, corrosive or toxic wastes

Do not use it for vacuuming

This machine is not suitable for work

have either a normal square pin plug

nitted, or a blue industrial plug.

such as petrol, or weed killer.

industrial plug inted.

















m Business Park

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

connections are dry and sate.

could catch fire.

5. Make sure that any extension cable

Unroll it fully or it will overheat and

where vehicles might run over it.

where it might be trapped, and places

sharp edges, doorways or windows

(160 feet). Put it directly into the rcd.

duty one, not longer than 50 metres

any special instructions given by the

it. Reset the rcd according to the

the rcd is working each time you use

shock if the cable or equipment gets

neip to protect you against electric

your equipment into the rcd. This will

əuı

2. Use the "TEST" button to check that

3. If you need extension cable, follow

λon

Ś

4. Lay it out carefully avoiding liquids,

suitable rated heavy

e əsn Ajuo pinous

not given any special

ріге сотралу ћаче

hire company. If the

instructions supplied with it.

230volt socket. Plug

device ("rcd") plugged

(SOUARE PIN OR BLUE PLUG)

connections are dry and safe.

4. Make sure that any extension cable

1. Use a residual current

230 VOLT EQUIPMENT

ojui

'suononusui

damaged.

qirectly

Hire Association Europe 2450 Regents Court The Crescent

olihull B37 7YE

1

catch tire.

.inemqiupe

44 (0) 121 380 4600

44 (0) 121 333 4109

fully or it will overheat and could

vehicles might run over it. Unroll it

be rapped, and places where

doorways or windows where it might

svoiding liquids, sharp edges,

between the transformer and the

must only use an extension cable

longer than 50 metres (160 teet). You

heavy duty 110v extension cable, not

you should only use a suitable rated

not given any special instructions

company. If the hire company have

not use any 230v extension cables.

1. If you are using a portable

110 УОЦТ ЕQUIPMENT (YELLOW PLUG)

Read the instructions below for your

square pin plug fitted, or a blue

directly into the 230 volt socket. Do

transformer, plug the transformer

Sh.

διλευ pλ the hire

any special instructions

WOIIOI (ADIC ADIC) TOIIOW

S. If you need to use an

.inemqiupe

.6nid isinanoni

3. Lay the extension cable out carefully

ae.org.u e.org.uk

Dry hands, switch off and unplug before emptying the waste container.

- 3.
- If you think the cable may be cut or damaged in any way, switch off and unplug 4. at the mains before inspecting it, if the cable attached to the vacuum cleaner is damaged, stop using the equipment. Contact the hire company. If an extension

cable has been damaged, do not use it again.

Keep this leaflet safe as it may be required for reference at a future date


Vacuum Cleaner - WET

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet **BEFORE you use the Vacuum Cleaner**



2. Water and electricity make a dangerous combination.



- This vacuum cleaner is designed for vacuum collection 3.
- of water and wet waste material.
- 4. The action of this vacuum cleaner can cause injury or damage if the equipment is not used in a careful and controlled way.
- Familiarise yourself with how the equipment works before starting work.
- 6. Plan and think ahead to make sure you will always be working safely.
- You should have at least the following items of protective equipment: rcd if using
- a 230 volt (mains) supply.
- 8. This equipment must not be used by minors, or by anyone under the influence of drugs or alcohol.
- This vacuum cleaner is designed for operation by an able bodied adult. Anyone with 9.





Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia





For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

Using the Vacuum Cleaner

1. Do not use the cleaner to vacuum dry waste

2.



Empty the waste container before it is full.