

Water Bowser

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the Water Bowser. IT IS NOT SUITABLE FOR DRINKING WATER.

- It is important that you read all of this leaflet and any others provided before using the water bowser.
- Water kept in this bowser is not suitable for drinking provided before using the water bowser.
- Moving this water bowser can cause injury or damage if not done in a careful and controlled way, especially if it contains water. Plan your work and think ahead to make sure that you are always working safely – read the
- recommendations in the "Using the water bowser" section of this leaflet. You must have at least the following items of personal protective equipment (ppe) whilst
 - moving or positioning the equipment:
 - Boots or protective footwear to a minimum EN345
 - **Rubberised Gloves**
- This water bowser must not be installed by minors, or by anyone under the influence of
- This water bowser is designed to be installed by an able bodied adult. Anyone with either temporary or permanent disability musk seek expert advice before doing so.
- Take care whilst loading/moving this equipment; in particular onto and off vehicles, as it weight is unevenly distributed. Observe good lifting practise and where possible, share the load.
 - Take care when using water under pressure.













www.hae.org.uk

















is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

Please keep this leaflet safely as it may be required for future reference

44 (0) 121 333 4109 44 (0) 121 380 4600

BAY 788 Iludilos The Crescent Birmingham Business Park nuou sinegen uce



Please keep it until you finish work. You may want to read this leaflet again. your insurer straight away cover, check with the nire company or 5. If you are in doubt about your insurance

will dive you any protection. involved in a highway accident, it is unlikely those normal insurance policies you cause damage to property belonging to a third party, or if you are 4. In addition, you should be aware that if

cover at an extra charge. Some hire companies will offer insurance

equipment yourself against theft

2. However, you must always secure the way to achieve this is by insurance.

damage such as vandalism, the best company against loss or unreasonable ednibment. You must indemnify the hire responsible for the safe custody of the 1. Under the terms of hire, you are

INSURANCE

a upping nazaru ามอรอบป and paths or other places which windows where they might get trapped, avoiding sharp edges, doorways or

water bowser, are laid out carefully 5. Ensure the hoses, when used with the where other people gather.

possible, away from roads, paths or utility services, and, where 4. Site the bowser away from electrical, and

not position the bower on uneven or used to prevent the wheels moving. Do firm level surface. Ensure the chocks are The water bowser should be sited on a

to keep away, place barriers around your associated with the movement of the water bowser. If appropriate warn others Protect other people from the

and that no one is near to you or could 1. Make sure that the area is clear and safe

USING THE WATER BOWSER

eed to use ppe Anyone working near to you will also



minimum of EN345. Safety boots or protective tootwear to a .muminim a se besu

protective equipment (ppe) must be 7. The following items or personal

SHOTARING

not the tow ball unit. break away cable – ensure this is fitted around your vehicles bar assembly and 11. The towing bar will be supplied with a

accelerate and turn than a venicle on its

when towing will take longer to stop. 10. You will need to be aware that a vehicle pressure regularly.

Check the condition of the tyres and tyre is removed when transporting the unit.

recommended that where possible liquid water which may be in the unit. It is









bowser should not generally exceed 85% have breaks fitted, the weight of When towing larger water bowsers that 750kg, whichever is less.

50% of the kerb weight of the car or breaks, the weight of the unit is limited to If you tow a smaller water bowser without

on motorways when towing. are not allowed to use the outside lane provided no lower limit is in force. You dual carriage roads and motorways, on single carriage roads, and 60 mph on When towing a water bowser you are restricted to a maximum speed of 50mph

engaged and used correctly. the towing bar and ball hitch are fitted, Ensure that any safety devices fitted to

tow nitch. methods of connecting to your vehicles regarding lighting boards and correct Observe the legal requirements

this bowser from your vehicle. Ensure that you observe the correct procedure for attaching and removing

your current driving licence and insurance allow you to do so. Before you tow this bowser, ensure that

DMING

